

FFDS (Flat Floor Dump Spread Body)



FFDS

Shown with optional spill shield, ladder, lights and tarp.



Standard Features:

- Available in 9' to 16' Lengths
- $\frac{3}{16}$ " Mild Steel Sides & Ends
- $\frac{3}{16}$ " Formed Dirt Shedding Top Rail
- $\frac{1}{4}$ " Long Sills, 14" in Height with Formed Cross Sills
- $\frac{1}{4}$ " Replaceable Floor, Supported on 12" Center
- Dual 6:1 Gear Box Drives
- 2" Drive & Idler Shafts with 2" Heavy Duty Bearings
- $1\frac{1}{4}$ " Heavy Duty Chain Adjusters
- Case Hardened Sprockets to 40-48 Rockwell
- 34" Wide Conveyor with $\frac{1}{2}$ " x $1\frac{1}{2}$ " Bar Flights on 4 $\frac{1}{2}$ " Centers
- Heavy Duty Pintle Chain with a 26,000 Minimum Tensile Strength
- Telescopic Double Acting Nitrided Hoist Cylinder
- Full Opening Double Acting Tailgate

Box Length	Side Height	Cubic Yard Capacity	CA Required	Hoist Capacity	Weight
10'	34"/40"/46"	8.0/9.5	84"	16 Ton Class 60	5240
11'	34"/40"/46"	10.0/11.5	96"	16 Ton Class 60	5764
12'	34"/46"	12.0/14.0	96" or 102"	25 Ton Class 60	6288
13'	34"/46"	13/15	108"	25 Ton Class 80	6812
14'	46"/54"	14/16	114"	25 Ton Class 80	7336
15'	46"/54"	15/17	126"	25 Ton Class 110	7860
16'	46"/54"	16/18	138"	30 Ton Class 110	8384
17'	46"/54"	17/19	---	---	---
18'	46"/54"	18/20	---	---	---

