

## 10.5 HP Engine or 11HP Honda or Single Hydraulic Motor Drive

### Standard Features:

- 8'-10' Hopper Length
- 50½" Width
- 2.5-3.9cu yd Capacities
- 12ga. Hopper Shell; 10ga. Formed Longsills Slotted for Drive and Idler Shaft Removal
- 1¼" Drive & Idler Shafts
- Heavy Duty 4-Bolt Flange Bearing
- Sloped Sides
- 20:1 Gear Box
- 6-Tooth Cast Iron Sprockets
- Inverted V
- Wireless Cab Control, Variable (10.5 HP Briggs & Stratton Engine)
- Hard Wired Control (11 HP Honda Engine)
- 4-Corner Lift System



Shown in Stainless Steel

### Options:

- 11 HP Honda Engine in lieu of 10.5 HP Briggs & Stratton
- ¼" or ⅜" Top Screens
- Turnbuckle Mounting Kit, Heavy Duty
- Binder Mounting Kit, Heavy Duty
- 6" Box Extension
- Center High Mounted Stop Light
- Bolt-On Spinner
- 12" Extended Spinner
- Extended Self-Loading Leg Kit
- Single Auger Discharge in lieu of Conveyor (Direct Drive Hydraulic)

	MD8-3850	MD9-3850	MD9-4450	MD10-3850	MD10-4450
Capacity	2.5 cu. yd.	2.8 cu. yd.	3.6 cu. yd.	3.1 cu. yd.	3.9 cu. yd.
Height	38"	38"	44"	38"	44"
Length	8'	9'	9'	10'	10'
Weight based on Engine	905	925	945	965	985



Shown in Mild Steel